

# 5CG8

## Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CG8 is the same as the 6CG8A except for the following items:*

Heater, for Unipotential Cathode:  
Voltage (AC or DC). . . . . 4.7 volts  
Current . . . . .  $0.6 \pm 6\%$  amp

# 5CL8A

## Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CL8A is the same as the 6CL8A except for the following items:*

Heater, for Unipotential Cathodes:  
Voltage (AC or DC). . . . . 4.7 volts  
Current . . . . .  $0.6 \pm 6\%$  amp

# 5CM8

## High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CM8 is the same as the 6CM8 except for the following items:*

Heater, for Unipotential Cathodes:  
Voltage (AC or DC). . . . . 4.7 volts  
Current . . . . .  $0.6 \pm 6\%$  amp



RADIO CORPORATION OF AMERICA  
Electron Tube Division  
Harrison, N. J.

DATA  
7-61